Euri Lighting

INSTALLATION GUIDE


MODEL#: EIN-CL39BN-2030e-2 / EIN-CL40WH-2030e-2



Questions?

For customer service please call us at 1-888-743-5766 Office Hours: 8:00 a.m. – 5:00 p.m. PST Monday-Friday

PLEASE REVIEW THE INSTRUCTIONS AND WARNINGS LISTED BELOW PRIOR TO PROPER INSTALLATION



WARNINGS CAUTIONS · Risk of fire / electrical shock • Do not look directly at the operating LED Module. LED Fixture installation requires knowledge of luminaire electrical • Do not touch this product with wet hands. systems. • Do not disassemble, repair or alter lamp. • Risk of electric shock – disconnect power at source before installation • Designed for indoor applications only. • Do not make or alter any open holes in an enclosure of wiring or • Suitable for damp locations. electrical components during installation. • The luminaires shall be grounded. • If lamp or luminaire exhibits abnormal operation (buzzing, flickering, Be careful not to touch the lamp pins to the metal housing minimal light, etc.), turn off power, remove lamp and contact us. For when installing. more information please visit www.eurilighting.com or call our toll-free This Device is not intended for use with emergency exits or number 1-888-743-5766. emergency lights. INSTALLATION INSTRUCTIONS Mounting the Cross Bar FIGURE 1 1. Make sure the power is turned off at main fuse/breaker. Junction box 2. Begin by screwing the two long mounting screws (B) into the crossbar (A). (Figure 1). Crossbar (A) 3. Mount crossbar (A) to junction box using the two short junction box 0. mount screws (C) provided. (Figure 1). Short junction Short junction box mounting screw (C) box mounting screw (C) Long mounting screw (B) Wiring Your Fixture FIGURE 2 1. Connect the black house wire (hot) to the black lamp fixture wire and secure with a wire connector (D), (Figure 2), House ground wire White house power wire 2. Connect the white house power wire (neutral) to the white lamp fixture Black house power wire Wire connector (D) wire and secure with a wire connector (D). (Figure 2) Só Wire connector (D) - White lamp fixture wire 3. Connect the copper lamp ground wire to an appropriate supply Black lamp fixture wire Fixture ground wire ground or a grounded junction box and secure with a wire connector (D). (Figure 2). 89 Q 89 Note: If fixture is mounted to a non-ferrous box, secure copper lamp around wire to around screw (labeled GND) on the Copper lamp ground wire Grou crossbar (A) as shown:

*Product may vary from illustrations depicted in the provided guide. Please proceed with caution. Installation by a qualified Electrician is recommended. ©2018. Euri Lighting | A Division of IRTRONIX Inc. All Rights Reserved

Euri Lighting

INSTALLATION GUIDE


MODEL#: EIN-CL39BN-2030e-2 / EIN-CL40WH-2030e-2



Questions?

For customer service please call us at 1-888-743-5766 Office Hours: 8:00 a.m. – 5:00 p.m. PST Monday-Friday

PLEASE REVIEW THE INSTRUCTIONS AND WARNINGS LISTED BELOW PRIOR TO PROPER INSTALLATION



WARNINGS CAUTIONS • Risk of fire / electrical shock • Do not look directly at the operating LED Module. LED Fixture installation requires knowledge of luminaire electrical • Do not touch this product with wet hands. systems. • Do not disassemble, repair or alter lamp. • Risk of electric shock – disconnect power at source before installation • Designed for indoor applications only. • Do not make or alter any open holes in an enclosure of wiring or • Suitable for damp locations. electrical components during installation. • The luminaires shall be grounded. • If lamp or luminaire exhibits abnormal operation (buzzing, flickering, Be careful not to touch the lamp pins to the metal housing minimal light, etc.), turn off power, remove lamp and contact us. For when installing. more information please visit www.eurilighting.com or call our toll-free This Device is not intended for use with emergency exits or number 1-888-743-5766. emergency lights. **INSTALLATION INSTRUCTIONS (continued)** FIGURE 3 FIGURE 4 4. After all wires are secure, place the fixtures over the outlet box and align the long mounting screws (B) with the two large ends of the keyholes. Twist the base until the heads of the long mounting screws (B) slide into the narrow ends of the keyholes. Secure the fixture by tightening the long mounting screws(B). (Figure 3). Installing the LED Module 🖉 👔 🖟 1. Line up the two pins on the base of the LED Module with the two holes in the mounting holes. (Figure 4). Long mounting screw (B) 2. Once in place, grasp the base of the LED module and twist until the LED module LED clicks into place. Securing the Fixture FIGURE 5 1. Screw the threaded mounting tube (E) into the base of the fixture. Place the glass shade over the base allowing the threaded mounting tube (E) to protrude through the bottom hole in the glass. (Figure 5). 2. Secure the glass shade to the fixture with the remaining nut (F). Place the bottom cap (G) onto the thread mounting tube and secure with the final (H), (Figure 5), Threaded mounting tube (E) Nut (F) -Bottom Cap (G) Finial (H)

*Product may vary from illustrations depicted in the provided guide. Please proceed with caution. Installation by a qualified Electrician is recommended. ©2018. Euri Lighting | A Division of IRTRONIX Inc. All Rights Reserved